

卷之三

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

ISSUE CLASSIFICATION	
Class	Subclass

U.S. UTILITY Patent Application

O.I.P.E.

PATENT DATE

SCANNED Wkmy Q.A. All 4

KC2 85

APPLICATION NO.	CONT/PRIOR	CLASS 564	SUBCLASS 710	ART UNIT 2841-2112 2841-2112	EXAMINER Worthy - Aunice PATER
09/964736			100		

APPENDIX

Mark Eidsom

三

Method and system for attaching multiple clock sources to an SDRAM memory array

PTO-2040
12/99

ISSUING CLASSIFICATION

Continued on Issue Slip Inside File Jacket

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				NOTICE OF ALLOWANCE MAILED	
	(Assistant Examiner)	(Date)			
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent No. _____				ISSUE FEE	
	(Primary Examiner)	(Date)		Amount Due	Date Paid
<input type="checkbox"/> The terminal _____ months of this patent have been disclaimed.				ISSUE BATCH NUMBER	
	(Legal Instruments Examiner)	(Date)			

WARNING:

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 388. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-438A
(Rev. 4/22)

FILED WITH: DISK (CRF) FICHE CD-ROM

(Attached in pocket on right inside flap)

(Attached in pocket on right inside flap)

(FACE)